Original Scientific Paper DOI: 10.7251/AGRENG1601113S UDC 551.311.21(55)

SOIL LOSS ESTIMATION OF S7-2 CATCHMENT OF THE SHIRINDAREH WATERSHED, IRAN USING THE RIVER BASIN MODEL

Velibor SPALEVIC¹*, Atefeh BEHZADFAR², Andre SILVA TAVARES³, Milena MOTEVA⁴, Vjekoslav TANASKOVIK⁵

^{1*}Department of Geography, Faculty of Philosophy, University of Montenegro, Montenegro ²Azad University, Science and Research Branch, Tehran, Iran
³Universidade Federal de Alfenas, Programa de Pós-Graduaçã-Ciências Ambientais, Brazil ⁴Agoretechnologies and Plant Protection "N. Pushkarov", Sofia, Bulgaria

⁵ Faculty of Agricultural Sciences and Food, University Ss. Cyril and Methodius in Skopje, Macedonia

*Corresponding author: velibor.spalevic@gmail.com

ABSTRACT

This study aims to estimate the soil loss of S7-2 Watershed of Shirindareh River Basin in Iran, using a simple but comprehensive "River Basin" model for erosion classification and prediction of erosion potential. Peak discharge from the S7-2 Watershed was calculated on 65 m³s⁻¹ for the incidence of 100 years; the net soil loss on 4397 m³km⁻², specific 178 m³ km⁻² per year. The results of the research and earlier application of the "River Basin" model in the studied area of the Shirindareh River Basin in Iran shown that this approach is a good tool for rapid assessment of erosion risk to support decision-making and policy development.

Keywords: soil erosion, river basin model, sediment yield, Shirindareh watershed.

INTRODUCTION

Soil loss is a serious ecological concern (Gholami *et al.*, 2016) in various environments worldwide (Kisic *et al.*, 2016; Ballesteros-Cánovas *et al.*, 2015; Stoffel and Huggel, 2012; Ristic *et al.*, 2001). Study of soil erosion and sediment yield in the watershed is one of the basic necessities to achieve integrated land management and soil and water conservation (Khaledi Darvishan *et al.*, 2014). Direct measurements of erosion in a watershed are possible with multi-years measurement of solid transport in the closing-section (Behzadfar *et al.*, 2014a and Behzadfar *et al.*, 2014b). The water and sediment sampling in given intervals need a lot of time and is costly (Khaledi Darvishan *et al.*, 2010), assessment of sediment yield using soil erosion models have been used more and more (Spalevic *et al.*, 2013a, 2013b, 2013c, 2013d). The modelling of the erosion process has progressed rapidly, and a variety of models have been developed to predict both runoff and soil loss.

We used the computer-graphic "River Basin" model of Spalevic (Spalevic, 2011; Spalevic et al., 2000; Spalevic, 1999) for prediction of soil erosion intensity from the watershed area.

MATERIAL AND METHODS

The study was conducted in the area of the S7-2 Watershed ($F = 25 \text{ km}^2$) of the Mountainous area of the Shirindareh River Basin, located in north eastern parts of Iran (Figure 1). he shortest distance between the fountainhead and the mouth, lv, is 10 km; and the total length of the main watercourse with tributaries is 54 km. The average slope gradient in the river basin, Isr, is calculated on 33% what indicates that in the river basin prevailing very steep slopes. The average river basin altitude Hsr, is calculated on 1480 m; the average elevation difference D, on 279 m. Basic climatological data: The volume of the torrent rain; Average annual air temperature; Average annual precipitation; needed for calculation of the soil erosion intensity and runoff from the River Basin were received from the meteorological stations located in North Khorasan province of Iran.

The geological analyses (geological formations of North Khorasan province, including those in the study area of the S7-2 watershed) were based on the research of the National Geological Survey Organization (NGS) of Bolourchi (1987).



Figure 1. Study area of the S7-2 watershed, the Shirindareh River Basin, Iran

The "River Basin" model (Spalevic et al., 2000; *link to the "River Basin" exe file available on: www.agricultforest.ac.me/Spalevic/River*) as a computer-graphic method, with the Erosion Potential Method – EPM (Gavrilovic, 1972) rooted in the procedure of this model, was used for soil loss estimation from the studied watershed. It gives a quantitative estimation of erosion intensity as well as the estimation of sediment production and transportation. According to the method sediment yield is calculated using the following calculation:

$$G_{yr \times sp^{/1}} = T \times H_{yr} \times f \sqrt{Z^3} \times R_u$$

where: $G_{yr sp}^{-1}$ – specific annual total erosion-induced sediment yield reaching the confluence, $m^3 yr^{-1} km^{-2}$; T – temperature coefficient of the watershed; H_{yr} – amount of rainfall, mm; – 3.14; Z – coefficient of erosion; R_u – coefficient of retention of soil in the watershed.

RESULTS AND DISCUSSION

The climate is continental, with the absolute maximum temperature of 34.6° C and the negative of -24.4° C, respectively. Average annual air temperature, t0, is 9.1° C and the Temperature coefficient of the region, T, is calculated on 1; The amount of torrential rain, hb, on 34.68 mm. The average annual precipitation, H_{yr}, is 317 mm (Source: Data from the North Khorasan Meteorological stations of Iran).

The studied area belongs to the Middle-East of the Kope-Dagh geographical region. The pastures and meadows are predominant and covering the area of 78%. A part under the forests is about 19% and ground without grass and arable land is of about 3% (Figure 2). The coefficient of the river basin planning is calculated on 0.62. The coefficient of the vegetation cover is calculated on 0.77.



Figure 2. Land use of the S7-2 watershed, the Shirindareh River Basin, Iran

The dominant erosion form in this area is **surface erosion** and is the most pronounced on the steep slopes without vegetation cover. Calculation of Sediment yield of the S7-2 Watershed of the Shirindareh River Basin of Iran is presented at the "River Basin" Report 1.

Report 1. The "River Basin" report for the S7-2 Watershed

Inputs: River basin area, **F**, 24.65 km²; The length of the watershed, **O**, 29.95, km; Natural length of the main watercourse, **Lv**, 9.98, km; The shortest distance between the fountainhead and mouth, **Lm**, 9.48 km; The total length of the main watercourse with tributaries of I and II class, **L**, 53.69 km; The area of the bigger river basin part, **Fv**, 14.27 km²; The area of the smaller river basin part, **Fm**, 10.38 km²; Altitude of the first contour line, **h0**, 1300 m; The lowest river basin elevation, **Hmin**, 1201 m; The highest river basin elevation, **Hmin**, 1201 m; The highest river basin elevation, **Hmax**, 1825 m; A part of the river basin consisted of a very permeable products from rocks (limestone, sand, gravel), **fp**, 0.15; A part of the river basin area consisted of medium permeable rocks (slates, marls, brownstone), **fpp**, 0.18; A part of the river basin under grass, meadows, pastures and orchards, **ft**, 0.78; A part of the river basin under basin under land, plough-land and ground without grass vegetation, **fg**, 0.03; The volume of the torrent rain, **hb**, 34.68 mm; Incidence, **Up**, 100 years; Average annual air

temperature, **t0**, 9.1 °C; Average annual precipitation, \mathbf{H}_{yr} , 317 mm; Types of soil products and related types, **Y**, 1.1; River basin planning, coefficient of the river basin planning, **Xa**, 0.62; Numeral equivalents of visible and clearly exposed erosion process, , 0.48.

Results: Coefficient of the river basin form, **A**, 0.59; Coefficient of the watershed development, **m**, 0.57; Average river basin width, **B**, 3.08, km; (A)symmetry of the river basin, **a**, 0.32; Density of the river network of the basin, **G**, 2.18; Coefficient of the river basin tortuousness, **K**, 1.05; Average river basin altitude, \mathbf{H}_{sr} , 1480.23 m; Average elevation difference of the river basin, **D**, 279.23 m; Average river basin decline, \mathbf{I}_{sr} , 32.99%; Coefficient of the region's permeability, S_1 , 0.86; Coefficient of the vegetation cover, S_2 , 0.77; Maximal outflow from the river basin, \mathbf{Q}_{max} , 65.06 m³s⁻¹; Production of erosion material in the river basin, \mathbf{W}_{yr} , 15191.9, m³ yr⁻¹; Coefficient of the deposit retention, **Ru**, 0.289; Real soil losses, \mathbf{G}_{yr} , 4397.7, m³ yr⁻¹; Real soil losses per km², 178.41 m³ yr⁻¹ km⁻².

This approach is also in use: Bosnia and Herzegovina, Brazil, Bulgaria, Croatia, Czech Republic, Italy, Macedonia, Montenegro, Morocco, Saudi Arabia, Serbia, South Africa and Slovenia (Al-Turki *et al.*, 2015; Gazdic *et al.*, 2015; Spalevic *et al.*, 2015a, 2015b, 2015c, 2015d, 2015e, 2015f, 2015g, 2015h, 2015i, 2015k; Vujacic & Spalevic, 2016; Kostadinov *et al.*, 2014; Spalevic *et al.*, 2014a, 2014b, 2014c, 2014d). The provided methodology have been successfully used in Iran in the regions of Chamgardalan, Kasilian, Kermanshah, Razavi Khorasan (Spalevic *et al.*, 2016; Draganic *et al.*, 2015a; Draganic *et al.*, 2015b; Behzadfar *et al.*, 2015; Barovic & Spalevic, 2015; Sadeghi, 2005) and other regions.

CONCLUSION

Calculation of sediment yield in the S7-2 Watershed showed the following results:

- Production of erosion material in the river basin, W_{yr} , was 15191 m³ yr⁻¹;

- Calculated soil losses are 4397 m³yr⁻¹ and Real soil losses were 178.41 m³ yr⁻¹ km⁻²;

- The peak discharge is 65 m³s⁻¹ (incidence 100yr).

This study confirmed the findings of Barovic *et al.* (2015); Behzadfar *et al.*, 2015, Zia Abadi & Ahmadi (2011); as well as Amiri (2010) in possibility of implementing "Erosion Potential Method" and the "River Basin Model" for the other river basins of the Caspian Sea, when hydrological stations are missing, taking into consideration the fact that the erosion modelling is cheaper than constructing hydrological stations. The results shown that this model is a good tool for rapid assessment of erosion risk to support decision-making and policy development.

REFERENCES

- Al-Turki, A.M., Ibrahim, H.M., Spalevic, V., (2015). Impact of land use changes on soil erosion intensity in Wadi Jazan watershed in southwestern Saudi Arabia. Agrosym 2015, Jahorina, Bosnia and Herzegovina; 10/2015
- Amiri, F. (2010). Estimate of Erosion and Sedimentation in Semi-arid Basin using Empirical Models of Erosion Potential within a Geographic Information System. Air, Soil and Water Research, 3: 37-44.
- Ballesteros-Cánovas JA, Czajka B, Janecka K, Lempa M, Kaczka R.J, Stoffel M. (2015). Flash floods in the Tatra Mountain streams: Frequency and triggers. Science of the Total Environment 511: 639–648.
- Barovic, G., Leandro Naves Silva, M., Veloso Gomes Batista, P., Vujacic, D., Soares Souza, W., Cesar Avanzi, J., Behzadfar M., Spalevic, V. (2015). Estimation of sediment yield using the IntErO model in the S1-5 Watershed of the Shirindareh River Basin, Iran. Agriculture and Forestry 61(3): 233-243
- Barovic, G. and Spalevic, V. (2015). Calculation of runoff and soil erosion intensity in the Rakljanska Rijeka Watershed, Polimlje, Montenegro. The 6th International Symposium Agrosym 2015, Jahorina, 15-18 October 2015, Bosnia and Herzegovina.
- Behzadfar, M., Curovic, M., Simunic, I., Tanaskovik, V., Spalevic, V. (2015). Calculation of soil erosion intensity in the S5-2 Watershed of the Shirindareh River Basin, Iran. International Conference on Soil, Tirana, Albania; 4-7 May, 2015.
- Behzadfar, M., Djurovic, N., Simunic, I., Filipovic, M., and Spalevic, V. (2014a). Calculation of soil erosion intensity in the S1-6 Watershed of the Shirindareh River Basin, Iran. International Scientific conference: Challenges in modern agricultural production, December 11, 2014, Skopje, Macedonia.
- Behzadfar, M. Tazioli, A., Vukelic-Shutoska, M., Simunic, I., and Spalevic, V. (2014b). Calculation of sediment yield in the S1-1 Watershed, Shirindareh Watershed, Iran. Agriculture and Forestry, 60 (4): 207-216.
- Bolourchi, M., Mehr Parto, M., and Afsharharb, A. (1987). Geological quadrangle map of Iran no. J5 (Bojnurd sheet), scale 1:250,000, Geological Survey of Iran.
- Draganic, J., Drobnjak, B., Campar, J., Bulajic, B., Zajovic, V., Behzadfar, M., Spalevic, V. (2015a). Calculation of Sediment yield using the IntErO Model in the S1-3 Watershed of the ShirinDareh River Basin, Iran. 9th Congress of the Soil Science Society of Bosnia and Herzegovina. November 2015, Mostar, Bosnia and Herzegovina.
- Draganic, J., Silva, M. L. N., Avanzi, C. J., Kisic, I., Spalevic, V. (2015b). Soil Loss Estimation using the IntErO Model in the S1-2 Watershed of the ShirinDareh River Basin, Iran. 9th Congress of the Soil Science Society of Bosnia and Herzegovina. November 2015, Mostar, Bosnia and Herzegovina.
- Gavrilovic, S., (1972). Inzenjering o bujicnim tokovima i eroziji. Izgradnja. Beograd.
- Gazdic, M., Pejovic, S., Vila, D., Vujacic, D., Barovic, G., Djurovic, N., Tanaskovikj, V., Spalevic, V. 2015. Soil erosion in the Orahovacka Rijeka

Watershed, Montenegro. The 6th International Symposium Agrosym 2015, Jahorina, Bosnia and Herzegovina.

- Gholami, L., Sadeghi, S.H.R., & Homaee, M. (2016). "Different effects of sheep manure conditioner on runoff and soil loss components in eroded soil", Catena, 139, 99-104.
- Kisic, I., Bogunovic, I., Birkas, M., Jurisic, A., Spalevic, V. (2016). The Role of Tillage and Crops in the Existence of the Soil. Archives of Agronomy and Soil Science, p: 1-11; DOI: 10.1080/03650340.2016.1213815.
- Khaledi Darvishan, A., Sadeghi, S.H.R., Homaee, M. and Arabkhedri, M. (2014). Measuring Sheet Erosion using Synthetic Color-Contrast Aggregates. Hydrological Processes, 28(15): 4463-4471.
- Khaledi Darvishan, A., Sadeghi, S.H.R. and Gholami, L. (2010). Efficacy of Time-Area Method in Simulating Temporal Variation of Sediment Yield in Chehelgazi Watershed, Iran. Annals of Warsaw University of Life Sciences, 42(1): 51-60.
- Kostadinov S, Zlatic M, Dragicevic S, Novkovic I, Kosanin O, Borisavljevic A, Lakicevic M, Mladjan D. (2014). Anthropogenic influence on erosion intensity changes in the Rasina river watershed Central Serbia. Fresenius Environmental Bulletin. 23(1a): 254-263.
- Ristic, R., Kostadinov, S., Malosevic, D., Spalevic, V. (2001). Erosion aspect in the assessment of soils of hydrologic classes and determination of CN number of runoff curve. Acta biologica Iugoslavica - serija A: Zemljište i biljka. 2001, vol. 50, No 3, p.165-174.
- Sadeghi, S. H.R. (2005). Semi-Detailed Technique for Soil Erosion Mapping Based on BLM and Satellite Image Applications. J. Agric. Sci. Technol. Vol. 7: 133-142.
- Spalevic, V., Barovic, G., Vujacic, D., Mijanovic, D., Curovic, M., Tanaskovic, V., and Behzadfar, M. (2016). Calculation of Sediment yield at the S 7-4 catchment of the Shirindareh Watershed of Iran using the River Basins model. Geophysical Research Abstracts. Vol. 18, EGU2016-6673, 2016. EGU General Assembly.
- Spalevic, V., Curovic, M., Barovic, G., Florijancic, T., Boskovic, I., Kisic, I. (2015a). Assessment of Sediment Yield in the Tronosa River Basin of Montenegro. The 9th International Symposium on Plant-Soil Interactions at Low pH. October 18-23, 2015, Dubrovnik, Croatia.
- Spalevic, V., Curovic, M., Barovic, G., Vujacic, D., Tunguz, V., Djurovic, N. (2015b). Soil erosion in the River Basin of Provala, Montenegro. Agrosym 2015, Jahorina, Bosnia and Herzegovina; 10/2015.
- Spalevic, V., Vujacic, D., Barovic, G., Simunic, I., Moteva, M. and Tanaskovik, V. (2015c). Soil erosion evaluation in the Rastocki Potok Watershed of Montenegro using the Erosion Potential Method. ISAF 2015, Faculty of Agricultural Sciences and Food – Skopje, 7-9 October, 2015, Ohrid, Macedonia.
- Spalevic, V., Frankl, A., Nyssen, J. Curovic, M. and Djurovic, N. (2015d). Calculation of soil erosion intensity in the Sutivanska Rijeka Watershed of

Montenegro using the IntErO model. 2nd International Symposium for Agriculture and Food - ISAF 2015, Faculty of Agricultural Sciences and Food – Skopje, 7-9 October, 2015, Ohrid, Macedonia.

- Spalevic, V., Curovic, M., Barovic, G., Vujacic, D., Djurovic, N. (2015e). Soil erosion in the River Basin of Kisjele Vode, Montenegro. International conference: Land Quality and Landscape Processes, Keszthely, Hungary; 06/2015
- Spalevic, V., Barovic, G., Vujacic, D., Bozovic, P., Kalac, I., Nyssen, J. (2015f). Assessment of soil erosion in the Susica River Basin, Berane Valley, Montenegro. International Conference on Soil, Tirana, Albania; 4-7 May, 2015.
- Spalevic, V., Barovic, G., Mitrovic, M., Hodzic, R., Mihajlovic, G., Frankl, A. (2015g). Assessment of sediment yield using the Erosion Potential Method (EPM) in the Karlicica Watershed of Montenegro. International Conference on Soil, Tirana, Albania.
- Spalevic, V., Blinkov, I., Trendafilov, A., Mukaetov, D., Djekovic, V., Djurovic, N. (2015h). Soil erosion assessment using the EPM method: A case study of the Ramcina River Basin, Montenegro. International Conference on Soil, Tirana, Albania; 4-7 May, 2015.
- Spalevic, V., Curovic, M., Vujacic, D., Barovic, G., Frankl, A., and Nyssen, J. (2015i). Assessment of soil erosion at the Brzava small watershed of Montenegro using the IntErO model. Geophysical Research Abstracts. Vol. 17, EGU2015-15007, 2015.
- Spalevic, V. Curovic, M. Tanaskovic, V., Djurovic, N., Lenaerts, T. and Nyssen, J. (2015k). Application of the IntErO model for the assessment of the soil erosion intensity and runoff of the river basin Dragovo Vrelo, Montenegro (invited speaker). Balkan Agriculture Congress, 8-10 September 2014. Edirne, Turkey.
- Spalevic, V., Curovic, M., Andjelkovic, A., Djekovic, V., Ilci, S. (2014a). Calculation of soil erosion intensity in the Nedakusi Watershed of the Polimlje Region, Montenegro. International conference: Challenges in modern agricultural production, December 11, 2014, Skopje, Macedonia.
- Spalevic, V., Tazioli, A. Djekovic, V., Andjelkovic, A., and Djurovic, N. (2014b). Assessment of soil erosion in the Lipnica Watershed, Polimlje, Montenegro. Agrosym 2014, Jahorina, 23-26 October 2014, Bosnia and Herzegovina, p 723-729.
- Spalevic, V., Hübl, J. Hasenauer, H. and Curovic, M. (2014c). Calculation of soil erosion intensity in the Bosnjak Watershed, Polimlje River Basin, Montenegro. Agrosym 2014, Jahorina, 23-26 October 2014, Bosnia and Herzegovina, p 730-738.
- Spalevic, V., Curovic, M., Billi, P., Fazzini, M. Frankl, A., and Nyssen, J. (2014d). Soil erosion in the Zim Potok Watershed, Polimlje River Basin, Montenegro. Agrosym 2014, Jahorina, 23-26 October 2014, Bosnia and Herzegovina, p 739-747.
- Spalevic, V., Djurovic, N., Mijovic, S., Vukelic-Sutoska, M., Curovic, M. (2013a). Soil Erosion Intensity and Runoff on the Djuricka River Basin (North of Montenegro). Malaysian Journal of Soil Science, Vol. 17: p.49-68.

- Spalevic, V., Curovic, M. Tanaskovik, V., Oljaca, M., Djurovic, N. (2013b). The impact of land use on soil erosion and run-off in the Krivaja river basin in Montenegro. The First International Symposium on Agricultural Engineering, 4th - 6th October 2013, Belgrade–Zemun, Serbia, VI: 1-14.
- Spalevic, V., Nyssen, J., Curovic, M., Lenaerts, T., Kerckhof, A., Annys, K. Van Den Branden, J., Frankl, A. (2013c). he impact of land use on soil erosion in the river basin Boljanska Rijeka in ontenegro. In proceeding of the 4th International Symposium Agrosym 2013, 3-6 October, 2013, Jahorina, Bosnia. Key note speakers, p. 54-63.
- Spalevic, V., Curovic, M., Uzen, N., Simunic, I., Vukelic-Shutoska, M. (2013d). Calculation of soil erosion intensity and runoff in the river basin of Ljesnica, Northeast of Montenegro. Proceeding, 24th Conference on Agriculture and Food Industry, Sarajevo.
- Spalevic, V. (2011). Impact of land use on runoff and soil erosion in Polimlje. Doctoral thesis, Faculty of Agriculture of the University of Belgrade, Serbia, p 1-260.
- Spalevic, V., Dlabac, A., Spalevic, B., Fušti , B., Popovi , V. (2000). Application of Computer-Graphic Methods in Studying the Discharge and Soil Erosion Intensity - I Programme "River Basins". Agriculture and Forestry, 46 (1-2): 19-36, Podgorica.
- Spalevic, V., Dlabac, A., Jovovic, Z., Rakocevic, J, Radunovic, M., Spalevic, B., Fustic, B. (1999). The Surface and distance Measuring Program. Acta Agriculture Serbica, Vol IV, 8, p.63-71.
- Stoffel, M., Huggel, C. (2012). Effects of climate change on mass movements in mountain environments. Progress in Physical Geography 36, 421–439.
- Vujacic, D., Spalevic, V. (2016). Assessment of Runoff and Soil Erosion in the Radulicka Rijeka Watershed, Polimlje, Montenegro. Agriculture and Forestry, 62 (2): 283-292.
- Zia Abadi, L., Ahmadi, H. (2011). Comparison of EPM and geomorphology methods for erosion and sediment yield assessment in Kasilian Watershed, Mazandaran Province, Iran. Desert, 16: 103-109.